

3Gb SAS-SAS/SATA RAID

E5412E

IT executives require significantly improved data storage infrastructure solutions for application and database archiving, e-mail, tiered storage, virtual tape libraries, and advanced data protection solutions. Addressing regulatory requirements, legal mandates, and improving disaster recovery along with much greater data storage power and volumetric efficiency have become critical success factors.

OEMs delivering solutions to meet these needs are also under pressure to address four key challenges: shorten time to market; reduce test, integration, warranty, and service costs; increase reliability; and bolster customer satisfaction. Xyratex RAID solutions reduce OEM development costs, feature enterprise-class RAID functionality including RAID 6 and Snapshot, ensure high availability, and they are highly reliable.

• Enhance Applications with Storage: Xyratex E5412E

The E5412E combines Serial Attached SCSI (SAS) connectivity with SAS (SAS) and Serial ATA (SATA) drive technology for cost effective, high performance storage solutions. It combines high performance connectivity, sophisticated storage management software, flexible interface support, and highly reliable storage devices to deliver a cost-effective, ultra-high performance OEM solution with the scalability and functionality necessary to meet the demands of today as well as tomorrow's rigorous applications environment. By leveraging the SAS full duplex, point-to-point architecture with dedicated connections, the E5412E delivers maximum data throughput, thereby providing faster, more responsive applications. In addition, the E5412E sustains maximum throughput (MB/s) for high bandwidth applications ranging from video editing to database-intensive online transaction processing.

Meanwhile, SATA-II drives in the E5412E provide the combination of high-capacity and cost-effective data storage normally found in nearline storage. Using SATA disks with their low cost-per-gigabyte design, the E5412E provides a cost-effective online repository for non-business-critical data, and offers the many advantages of tiered storage to the Small and Medium Business (SMB) market. Xyratex E5412E sets new standards for entry-level RAID storage offerings.

• Managing Storage From A Single Pane of Glass

Xyratex's StorView software configures and administers the E5412E storage system, and distinguishes it from other entry-level systems on the market today. Automated control of individual controller's cache, arrays and devices via a web-based interface simplifies storage administration, while StorView's full-function Command Line Interface (CLI) allows integration of array management into existing operational procedures. An optional upgrade to StorView Global Manager enables configuration, monitoring and management of any 5000 Series RAID controller from any location, anywhere on the network.



Features

- Single (2) or Dual (4) 3Gb/s 4-lane SAS host connections per system
- Mix up to 60 high performance SAS and cost effective SATA-II drives
- Snapshot support for up to 192 snaps
- StorView™ controller based management software
- Full RAID 6 & Snapshot support
- Dual active high availability and low cost single controller configurations
- Host based dynamic multi-pathing for high availability
- Exceptional expandability with 60TB of total capacity
- Online capacity growth through dynamic array and LUN expansion
- Redundant modular design with hot-swappable components

3Gb SAS-SAS/SATA-II RAID E5412E

• Technical Specification

General Information

Product Code	RS-1220-E3-5412E
External Interface	3Gb 4-lane SAS connection via LSI SAS3442x SAS HBA
Supported Operating Platforms	Windows 2003 (IA32, EM64T, IA64); RedHat Linux AS3/AS4 (IA32, EM64T, IA64); SuSE Linux 9/10 (IA32, EM64T, IA64), Solaris 10)
Supported Hosts	256, 512 LUNs, LUN Masking, >2TB LUNs
Total Capacity/Unit	12TB
Expansion Chassis	RS-1220-E3-XPN (4 max), SAS connected (SFF-8470), single & dual IO module configs
Total Expansion Capacity	60TB, 512MB & 1GB cache per controller (selectable by volume: read, adaptive read-ahead, write through, write-back), battery backup

Disk Drives

Disk Drives Supported	SAS (15K/73GB/146GB/300GB), SAS (10K/400GB), SATA (7.2K/250GB/500GB/750GB/1TB)
Interface Types	SAS (3Gb/s), SATA-II (3Gb/s), NCQ, dedicated bandwidth to each drive
Max Drives per Enclosure	12, 512 Logical Drives/system, automatic bad sector assignment

RAID Controllers

No. RAID Controllers	1 (single) or 2 (dual – HA)
RAID Levels Supported	Up to 60 disk arrays with independent RAID level 0, 1, 5, 6, 10, and 50 support, selectable strip sizes (64, 128, & 256K)
RAID Protection Features	Background initialization, background parity checking, and automatic drive rebuild with redundant RAID arrays

System Management

Software	StorView, StorView Global, StorView Path Manager
Interfaces Supported	Ethernet (out-of-band), FC host based (in-band), Xyratex Command Line Interface (CLI) for RAID

System Availability

Hot Swappable Components	Disk drives, RAID controllers, power supplies and cooling module
Additional Reliability Features	StorView Path Manager – Windows host based dynamic multi-path failover

Dimensions

Height	87.9mm (3.46") 2 EIA units
Width	443.7mm (17.49") 1EC rack compliant
Depth	550mm (21.65")
Weight	32.2Kg (71 lbs.) dual controller configuration with drives

Electrical: AC Input

Voltage	100-240 VAC @ 50/60 Hz. Single Phase
Input Current	6.0A (115 VAC), 3.0A (230 VAC)
Input Power	300W Typical

Electrical: DC Input

Voltage	-40 to -60 VDC
Input Current	
Input Power	

Environmental: Operating

Temperature	5° to 40°C (41° F to 104° F)
Humidity	8% to 80% (non condensing)
Altitude	2,133m (7,000 ft)
Shock	5g 10ms ½ sine
Vibration	Random .21 grms 5-500Hz
Acoustics	<58 dB LpA @20° C

Environmental: Non-Operating

Temperature	1° to 50°C (33.8° to 122° F)
Humidity	8% to 80% (non-condensing)
Altitude	12,192m (40,000 ft)
Shock	30g 10ms ½ sine
Vibration	Random 1.04 grms 2-200Hz

Approvals

CCC, BSMI, CE, UL, cUL, RoHS (R5), Microsoft WHQL, Microsoft RAID System Submission – MPIO (2-Node Cluster)

Warranty Information

Enclosures with drives Up to 3 years. Please contact Xyratex for detailed warranty information.

Environmental Standards



ISO 14001: 2004 Cert No. EMS91560



USA Sales & Support

T +1 887 997 2839
T +1 887 XYRATEx

UK HQ

T +44(0)23 9249 6000
F +44(0)23 9249 2284

©2007 Xyratex (The trading name of Xyratex Technology Limited). Registered in England & Wales. Company no: 03134912. Registered Office: Langstone Road, Havant, Hampshire PO9 1SA, England. The information given in this brochure is for marketing purposes and is not intended to be a specification nor to provide the basis for a warranty. The products and their details are subject to change. For a detailed specification or if you need to meet a specific requirement please contact Xyratex: www.xyratex.com.